

## Installation Instructions for: Rear Differential Cover (Honda VT1100)

### Please follow these instructions carefully!

#### Package Contents

- Ring cover, Screw, Nut, 5/32" Hex key and Instructions

#### Tools you will need to provide:

- 7/16" or adjustable wrench or pliers.

Please read over the entire installation process before beginning the installation. The install procedure should take a few minutes.

#### Installing the *Rear Differential Cover*:

1. Orient the cover so that the "bump" is towards the rear of the bike when holding the 1/2" mounting flanges vertical (as shown in the photo to the right).
2. Spread open the ring cover so that you may carefully slide it over the top of the differential case. Insert the screw through the mounting flange, and start the nut with your fingers. Tighten the nut a little using your wrenches until ring is "snug", but you can still move it.
3. Make sure the "bump" of the cover is aligned with the "bump" of the gray plastic cover. Also, pull the chrome cover towards you to make sure it is flush against the edge of the Rear Differential metal casing.
4. Tighten the screw until the ring is secure. Do not over-tighten. Just make it snug, so that if you grab onto the ring, you cannot move it. (When properly tightened, it should resemble the photo at the right.)



5. Congratulations! You are done.



**Care of your cover:** Never use an abrasive cleaner. You may wash and wax as you would with any piece of chrome steel.